



<p>DESCRIPTION</p>	<p>PureCast 605 is a two-component liquid castable polyurethane elastomer that contains no TDI or MOCA. The material when cured has outstanding physical properties. Exhibiting high tensile and tear strength along with exceptional abrasion resistance. It is insensitive to typical environmental moisture and exhibits low shrinkage. The product is reddish/brown in color.</p>																																																																					
<p>MIXING AND APPLICATION</p>	<p>Condition the liquid components: Component A to 90°F-100°F to reduce viscosity which greatly aids with mixing and Component B to 72°F before combining. Warmer temperature will significantly shorten the working time and colder temperatures will lengthen time and make mixing difficult.</p> <p>In a clean plastic container, mix by Weight 100 parts of Component A (clear) and 31 parts Component B (black or clear amber) or mix by Volume 100 parts Component A and 32 part Component B.</p> <p>Start mixing immediately after A & B components are added to the beaker. Use a clean flat spatula taking care to scrape the sides and bottom of the container to include all of the unmixed material.</p> <p>Mix for 1 minute, mixture should be evenly mixed with no "lines" of unmixed clear or black.</p> <p>Pour mixture into prepared mold. Cami 980 silicone mold release is recommended for most surfaces.</p> <p>Clean up with mineral spirits.</p> <p>Metallic surfaces to be bonded should be brushed blasted to achieve a 2 to 3-mill surface profile to remove all surface oxidation and traces of previously bonded polymer. After blasting, etched surface should be thoroughly degreased using clean Toluene or mineral spirits solvent wipe. Surface is now ready for priming.</p> <p>To prevent further surface oxidation, prepared metallic surface should be immediately primed using Primer 460 SPX or Primer 800 and allowed to cure in a dry environment overnight for 12 hours. This should be allowed to cure for 1 hour at 72° F before applying PureCast 605 urethane elastomer (see Primer 460 SPX or Primer 800 technical data sheet for full mixing and application instructions).</p> <p>Do not allow Primer 460SPX or Primer 800 to cure longer than 6 hours before applying PureCast 605 urethane elastomer to ensure a total chemical bond in between primer and elastomer coating.</p> <p>Maintain at least 72° F during the complete application process. Colder temperatures retard curing times, warmer temperatures reduce curing times.</p> <p>All primed surfaces should be kept free of moisture, dust and any grease or oil, which may interfere with polymer bond.</p>																																																																					
<p>PHYSICAL PROPERTIES</p>	<table border="0"> <tr> <td>Mix Ratio By weight</td> <td></td> <td>100 parts A/ 13 part B</td> </tr> <tr> <td>Mix Ratio By volume</td> <td></td> <td>100 parts A/ 14 parts B</td> </tr> <tr> <td>Viscosity @ 72°F (A Side)</td> <td></td> <td>7,000 CPS</td> </tr> <tr> <td>Viscosity @ 72°F (B Side)</td> <td></td> <td>100 CPS</td> </tr> <tr> <td>Viscosity @ 72°F (Mixed)</td> <td></td> <td>4000 CPS</td> </tr> <tr> <td>Color</td> <td>Part A:</td> <td>Clear</td> </tr> <tr> <td>Color</td> <td>Part B:</td> <td>Clear to Clear Amber</td> </tr> <tr> <td>Color</td> <td>Mixed:</td> <td>Clear to Clear Amber</td> </tr> <tr> <td>Working Life @ 72°F</td> <td></td> <td>15-25 minutes</td> </tr> <tr> <td>Demold Time* @ 72°F</td> <td></td> <td>8-10 hours</td> </tr> <tr> <td>Demold Time* @ 150°F</td> <td></td> <td>1-2 hours</td> </tr> <tr> <td>Complete Cure* @ 72°F</td> <td></td> <td>7 days</td> </tr> <tr> <td colspan="3">* Set time and Demold time depends on temperature and relative humidity.</td> </tr> <tr> <td>Specific Gravity: (Part A)</td> <td></td> <td>1.03</td> </tr> <tr> <td>Specific Gravity: (Part B)</td> <td></td> <td>1.02</td> </tr> <tr> <td>Specific Gravity: (Mixed)</td> <td></td> <td>1.03</td> </tr> <tr> <td>Weight/Gallon Part A</td> <td></td> <td>8.59 lbs.</td> </tr> <tr> <td>Weight/Gallon Part B</td> <td></td> <td>8.50 lbs.</td> </tr> <tr> <td>Weight/Gallon Mixed</td> <td></td> <td>8.59 lbs.</td> </tr> <tr> <td>Hardness @ 72° F</td> <td>ASTM 2240-85</td> <td>50-60 Shore D</td> </tr> <tr> <td>Tensile Strength</td> <td>D-412 die C</td> <td>6,284 psi</td> </tr> <tr> <td>Elongation</td> <td>D-412 die C</td> <td>357%</td> </tr> <tr> <td>Tear Strength</td> <td>D-624 die C</td> <td>1221 lb./in.</td> </tr> </table>	Mix Ratio By weight		100 parts A/ 13 part B	Mix Ratio By volume		100 parts A/ 14 parts B	Viscosity @ 72°F (A Side)		7,000 CPS	Viscosity @ 72°F (B Side)		100 CPS	Viscosity @ 72°F (Mixed)		4000 CPS	Color	Part A:	Clear	Color	Part B:	Clear to Clear Amber	Color	Mixed:	Clear to Clear Amber	Working Life @ 72°F		15-25 minutes	Demold Time* @ 72°F		8-10 hours	Demold Time* @ 150°F		1-2 hours	Complete Cure* @ 72°F		7 days	* Set time and Demold time depends on temperature and relative humidity.			Specific Gravity: (Part A)		1.03	Specific Gravity: (Part B)		1.02	Specific Gravity: (Mixed)		1.03	Weight/Gallon Part A		8.59 lbs.	Weight/Gallon Part B		8.50 lbs.	Weight/Gallon Mixed		8.59 lbs.	Hardness @ 72° F	ASTM 2240-85	50-60 Shore D	Tensile Strength	D-412 die C	6,284 psi	Elongation	D-412 die C	357%	Tear Strength	D-624 die C	1221 lb./in.
Mix Ratio By weight		100 parts A/ 13 part B																																																																				
Mix Ratio By volume		100 parts A/ 14 parts B																																																																				
Viscosity @ 72°F (A Side)		7,000 CPS																																																																				
Viscosity @ 72°F (B Side)		100 CPS																																																																				
Viscosity @ 72°F (Mixed)		4000 CPS																																																																				
Color	Part A:	Clear																																																																				
Color	Part B:	Clear to Clear Amber																																																																				
Color	Mixed:	Clear to Clear Amber																																																																				
Working Life @ 72°F		15-25 minutes																																																																				
Demold Time* @ 72°F		8-10 hours																																																																				
Demold Time* @ 150°F		1-2 hours																																																																				
Complete Cure* @ 72°F		7 days																																																																				
* Set time and Demold time depends on temperature and relative humidity.																																																																						
Specific Gravity: (Part A)		1.03																																																																				
Specific Gravity: (Part B)		1.02																																																																				
Specific Gravity: (Mixed)		1.03																																																																				
Weight/Gallon Part A		8.59 lbs.																																																																				
Weight/Gallon Part B		8.50 lbs.																																																																				
Weight/Gallon Mixed		8.59 lbs.																																																																				
Hardness @ 72° F	ASTM 2240-85	50-60 Shore D																																																																				
Tensile Strength	D-412 die C	6,284 psi																																																																				
Elongation	D-412 die C	357%																																																																				
Tear Strength	D-624 die C	1221 lb./in.																																																																				
<p>WORKING PROPERTIES</p>																																																																						



STORAGE AND SHELF LIFE	PureCast 605 is shipped from the factory in sealed containers. The containers should be stored in a cool, dry area that is protected from direct sunlight and moisture. Storage temperatures should not exceed 80°F. The shelf life of the factory sealed containers stored under these conditions is six months. Containers that have been opened should be resealed immediately after material has been removed in order to prevent solvent evaporation.
SHIPPING CLASS	Class 55 Non-hazardous